



All Valtti wood oils are suitable for impregnated wood, hardwood, and thermally modified and untreated wood, as well as wood that has been industrially oiled or previously treated with oil.

Application

1. Wash the old, darkened wood surface with Tehopesu (Super Clean) in accordance with the instructions on the label, and allow to dry.
2. Stir the wood oil thoroughly before use and occasionally during use.
3. Spread the wood oil with a decking oil spatula, brush, or sponge, pressing the tool down tightly so that all the oil is absorbed into the wood. Wipe off any excess oil.

General

Every year, check the condition of the surfaces treated with oil. If necessary, apply a maintenance treatment when the surface looks dry and faded. Open deck surfaces may require a maintenance treatment every 1–4 years, depending on the product used.

Use tinted wood oil, because a tinted product withstands weathering better than a colorless product. The type and condition of wood affect the final color. Test the product on a small area first.

Please note! Risk of self-ignition of cleaning rags and cotton waste used with wood oil or sanding dust containing the product. Such materials should be stored soaked in water before disposal, preferably dried outdoors in an open area or burned immediately.



860115 MIES VAPOC000 / 2016



www.tikkurila.com

Tikkurila Oyj, P.O. Box 53, FI-01310 Vantaa Finland, Tel. +358 20 191 2000, www.tikkurila.com



VALTTI® WOOD OILS

MAINTAIN THE NATURAL BEAUTY OF WOOD

NEW! The special pigmented, water-borne Valtti Plus Terassiöljy (Terrace Oil) is even more durable than before. Available in the familiar standard colors: brown, black, and gray!



