



TIKKURILA

PARKETTI-ÄSSÄ

Durable beauty for wooden floors

Protect your wooden floors and make them durable with Tikkurila low-odour waterborne Parketti-Ässä parquet lacquer. Improved Parketti-Ässä quality gives even better crack and wear protection. Prime the floor with Parketti-Ässä Stain to match your interior decoration.



PARKETTI-ÄSSÄ -product family

Floor has an important impact in the feeling of your home. Genuine wood under the feet increases cosyness and intimacy. Parquet or plank floor is also an expensive investment. Therefore it is worth proper handling from the beginning. Parketti-Ässä product family is now improved and easier to use.

- No need for separate priming lacquer, use same product for priming and finishing
- Improved shock and wear resistance
- Neutral colour - no yellowing of the substrate
- Quick drying - ready floor during one working day
- Also roller application - easier and faster work
- Fast hardening
- Gloss, semi-gloss and new semi-matt

Parketti-Ässä Floor Lacquer

Waterborne polyurethane-acrylate lacquer for interior use. Suitable for parquet and wood flooring. Available as gloss, semi-gloss, and a novelty, semi-matt. Easy to pour onto floor from handy plastic canisters. Coverage 8-25 m²/l, due to the working method.

Parketti-Ässä Stain

Waterborne, tintable acrylate stain. To be used for staining sanded or plain wooden floors together with Parketti-Ässä Floor Lacquer. Coverage 15-25 m²/l, depending on the working method. Tinting according to Interior Wood Stains and Lapponia colour cards.



TIPS FOR SUCCESS

PRETREATMENT

New clean floors:

Clean the surface from dirt and dust. Moisten it lightly with water, let dry and sand down uprisen wood fibres. Remove sanding dust.

Old worn or previously lacquered floors:

Clean previously treated slightly worn floor surface from dirt, wax and grease. Sand the surface gently matt and remove sanding dust. Sand down outworn floor surface mechanically until clean wood. Dust off carefully.

LACQUERING

Mix Parketti-Ässä Floor Lacquer by shaking the canister before use and occasionally during application.

Prime parquet floor with Parketti-Ässä Floor Lacquer 2-3 times applying the lacquer with reinforced steel trowel. Sand the surface after the first lacquering. Finish with Parketti-Ässä Floor Lacquer 2-3 times using flotex or mohair trowel or alternatively 1-2 times with a roller (roller application only for semi-gloss or semi-matt lacquer). Uneven boarded floors can be varnished directly with a brush. If you tint the floor with Parketti-Ässä Stain, spread it thinly with flotex-trowel on clean wood floor instead of priming. Apply 2 layers of stain and finish with lacquer as advised.

Maintenance treatment:

Varnish previously treated, slightly worn floors with Parketti-Ässä Floor Lacquer 2-3 times using flotex or mohair trowel or 1-2 times with a roller.





TIKKURILA



TIKKURILA OYJ

PL/PO Box 53, FI-01301 Vantaa, Puh./Tel. +358 20 191 2000
www.tikkurila.com